

2xOF1202-40MQ6 Oil Free Compressor with Dryer





Features

- 100% oil free
- 100% duty cycle
- Low noise and vibration level
- Easy maintenance
- Long-life, 2-year warranty
- 8000 hours cup life at 8bar
- 4000 hours maintenance interval for the dryer

Description

- Built-in 2-column adsorption dryer
- Pressure dew point down to -40°C
- 1µm air filtration (class 2 for dust according to ISO8573.1:2001)
- Pressure regulator included
- Receiver with internal coating and 5-year warranty

Other Versions


• Without dryer: 2xOF1202-40M

• Other power supply: 400V - 3 phases

Product Specifications

Model	2xOF1202-40MQ6		
Voltage	V	1x230	1x230
Frequency	Hz	50	60
Motor	HP	4	4
	kW	2.94	2.94
Displacement	l/min	580	658
Air flow @ 8bar	l/min	208	234
	cfm	7.35	8.3
Max. pressure	bar	8	8
	psi	120	120
Max. current	А	16	18
Receiver volume	litres	40	40
	gallon	10.6	10.6
Weight	kg	179	179
	lbs	395	395
Noise level	dB(A)/1m	63	66
Duty cycle		100%	100%

Air Flow / Pressure Curve*



*air flow is reduced by approx. 18-20% on units with dryer

Dimensions*

