


2xOFI 202-150B (oil-less)

Voltage	V	200	200	230	240	3x400	3x440						
Frequency	Hz	50	60	50	60	50	60						
Motor	HP	4.00	4.00	4.00	4.00	4.00	4.00						
	kW	2.94	2.94	2.94	2.94	2.94	2.94						
Displacement	l/min	580	656	580	656	580	656						
	CFM	20.48	23.17	20.48	23.17	20.48	23.17						
FAD @ 8 bar	l/min	260	292	260	292	260	292						
	CFM	9.18	10.31	9.18	10.31	9.18	10.31						
Max. pressure ¹⁾	bar	8	8	8	8	8	8						
	psi	120	120	120	120	120	120						
Max. current	A	-	-	16.0	18.0	10.0	10.0						
Tank size	litres	150	150	150	150	150	150						
	gallon	39.6	39.6	39.6	39.6	39.6	39.6						
Weight	kg	129	129	129	129	129	129						
	lbs	284	284	284	284	284	284						
Noise level	dB(A)/1m	79	78	79	78	79	78						
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes						
Duty cycle		100%	100%	100%	100%	100%	100%						



Dimensions (l x w x h)
1250 x 541 x 873 mm / 49²/₈ x 21²/₈ x 34³/₈ inch

¹⁾ Higher pressure available upon request

Technical modifications reserved



JUN-AIR®

E-mail: info@jun-air.dk
Internet: www.jun-air.com